

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
17 March 2005 (17.03.2005)

PCT

(10) International Publication Number
WO 2005/023542 A1

(51) International Patent Classification⁷: **B32B 27/34**,
F16L 11/04, 9/12

Heidelberg (DE). **VIERNEISEL, Thomas** [DE/DE];
Bensheimer Strasse 7, 64625 Bensheim (DE).

(21) International Application Number:
PCT/EP2004/010059

(74) Agent: **STEIMLE, Josef**; Dreiss, Fuhlendorf, Steimle & Becker, Postfach 103762, 70032 Stuttgart (DE).

(22) International Filing Date:
9 September 2004 (09.09.2004)

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English
(26) Publication Language: English

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(30) Priority Data:
103 41 988.8 9 September 2003 (09.09.2003) DE

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



WO 2005/023542 A1

(54) Title: MULTI-LAYER FUEL- AND VAPOR TUBE COMPRISING POLYPHTHALAMIDE

(57) Abstract: The invention is concerned with multilayer tubes for use in a vehicle, containing at least one Polyphthalamide-layer, which can be used as fuel or vapor tube in a vehicle.

Title: Multi-layer fuel- and vapor tube comprising Polypythalamide

Description

5

The invention is concerned with multilayer tubes for use in a motor-vehicle.

Large strains (e.g. bending, elongation) are expected against
10 fuel lines and therefore high technical standards are required.

In the state of the art fuel and vapor tubes consisting of polyamides are described. It is increasingly important, that
15 the used tubes are essentially impermissible against fluid emissions (e.g. hydrocarbons in fuels).

Thus a hydrocarbon permission level for such a tube of equal or below 0,5 g/m² for a time frame of 24 h (1 d) is required. Furthermore, it is required, that the used fuel tubes do not
20 have interactions with existing materials within the fuel, like oxidants, detergents, tensides and additives (e.g. ethanol, methanol, etc.)

Moreover penetration of fluids may lead to crystallisation of
25 tubing material (e.g. when using Nylon 11, Nylon 12, in particular in presence of copper ions) and blocking of the tube.

For those reasons multilayer tubes are of particular interest. However, it is difficult to obtain satisfactory laminate characteristics between dissimilar polymeres, as
30 given in the case of a multilayer tube.

Particularly one object of the invention is to provide a novel barrier layer having stable carrier characteristics in the
35 frame of multilayer tubes.

The object is solved by a multilayer tube having the features of claim 1, in particular a multilayer tube comprising at least one Polyphthalamide layer, being used as fuel- or vapor tube. Further embodiments result from the appropriate sub-
5 claims.

According to the invention the term „tube“ is to be understood as a functional synonym or equivalent corresponding to "hose" or "line".

10 "Multilayer tube" means a tube consisting of at least two layers. More preferably the tube consists of three and more layers, most preferably 3 - 5 or 6 layers (cf. embodiments in detail below); further layers are also possible.

15 According to the present invention at least one Polyphthalamide (in short: PPA) layer is a suitable barrier layer of the tube, preferably comprising one or more Polyamide layer.

20 If necessary in combination with a bonding layer, preferably selected from a polyamide.

Polyamides are preferably selected from the group consisting of 6,6-Polyamide (in short: PA 6), 11,11-Polyamide (in short:
25 PA 11), 12,12-Polyamide (in short: PA 12), Copolymer derived from 6,6-Polyamide and 12,12-Polyamide (in short: PA 6/12).

Layers consisting of Polyethylene (in short: PE) or Polypropylene (in short: PP) or a Copolymer thereof may also
30 contain.

Moreover, PPA layer(s) thinner than other layers, in particular Polyamide layers, are preferred.

35 In a further preferred embodiment according to the invention the outer layer and/or inner layer consists of PPA. This

depends on the fact, that embodiments having PPA - intermediate layer exhibit less laminate characteristics than those embodiments comprising PPA- inner and / or outer layer.

5 A further embodiment relates to a multilayer tube according to the invention, wherein at least one layer, in fact PPA- or PA-layer is conductible.

The conductivity of the tube may be provided for example (non-complete listing) by the means of surcharges of carbon
10 (also carbon black) or metals (Cu, Si, Ag, Au, Ni etc.).

In the following such a conductive layer is denoted as PPA cond. or PA cond..

15 The multilayer tubes prove to be stable and strainable, also respectively bending and elongation under maintenance of the laminate characteristics.

Hence, an especial embodiment concerns a multilayer tubing,
20 comprising at least one PPA-layer and at least one Polyamide, non-completing selected from the group having the layers:

PPA - PA 6 - PA 6/12 (bonding agent) - PA 12,

PPA - PA 6 - PA 6/12 (bonding agent) - PPA,

25 PPA - PA 6/12 (bonding agent) - PA 12,

PA 6 - PPA - PA 6,

PA 12 - PPA - PA 12,

PPA - PA 6 (bonding agent) - PPA,

PPA cond. - PPA - PA 6 (bonding agent) - PPA.

30

(notation from inner layer - outer layer)

Within this group, embodiments having PPA as outer and / or inner layer are prefered.

Most advantegous are the high temperature resistance, chemical inert properties, flexibility of the performance, good adhesion.

5 Especially advantageous are the high temperature constancy, chemical inertness, flexibility of tubes, as well as good layer adhesion as well as good permeation constancy.

In contrast to pure polyamide tubes a temperature constancy
10 of up to 140° Celsius can be achieved.

The multilayer tubes according to the invention can be used for all types of conventional fuel and petrol or vapors (including gases) and are obtainable in every desired length and thickness (diameter as well as wall thickness).

15 The tube materials mentioned in this context are exclusively materials that can be commercially acquired in trade. The tube materials indicated are all easily extrudable, if necessary co-extrudable and easily accessible to fusion
20 processing as thermoplastic materials. The layers adhere to one another due to permanent laminar adhesion, if necessary supported by means of a bonding agent or an adhesive (e.g. glue as well). All embodiments of the multilayer tubes as per the invention can be manufactured by the person skilled in
25 the art in a known manner.

In a further embodiment the layers can contain additions, i.e. the usual softeners, flame restraints and anti-oxidation means or stabilising agents.

30 The multiplayer tubes as per the layer in question can optionally contain an outer cover, which e. g. consists of a adequate thermoplastic suitable for fusion processing, which is either co-extruded or attached, for the purpose of an
35 additional isolation (protection). Furthermore, this layer may be able to lead off electrostatic energy. According to

the invention such an outer cover shall be not read as a synonym for outer layer.

Furthermore the invention, and not finally, is concerned
5 with such conductive and non-conductive layer combinations as follows, wherein the term "BA" designates "Bonding agent"
(adhesive) :

Nicht leitfähig / Non conductive

PPA	PE	
PPA	PP	
PPA	PA 6	
PPA	PA 11	
PPA	PA 12	
PE	PPA	
PP	PPA	
PA 6	PPA	
PA 11	PPA	
PA 12	PPA	
PPA	BA	PPA
PPA	BA	PE
PPA	BA	PP
PPA	BA	PA 6
PPA	BA	PA 11
PPA	BA	PA 12
PE	BA	PPA
PP	BA	PPA
PA 6	BA	PPA
PA 11	BA	PPA
PA 12	BA	PPA
PPA	PA 6/12	PPA
PPA	PA 6/12	PE
PPA	PA 6/12	PP
PPA	PA 6/12	PA 6
PPA	PA 6/12	PA 11
PPA	PA 6/12	PA 12

PE	PA 6/12	PPA
PP	PA 6/12	PPA
PA 6	PA 6/12	PPA
PA 11	PA 6/12	PPA
PA 12	PA 6/12	PPA
PE	PPA	PE
PP	PPA	PP
PA 6	PPA	PA 6
PA 11	PPA	PA 11
PA 12	PPA	PA 12
PE	PPA	PP
PE	PPA	PA 6
PE	PPA	PA 11
PE	PPA	PA 12
PP	PPA	PE
PA 6	PPA	PE
PA 11	PPA	PE
PA 12	PPA	PE
PP	PPA	PA 6
PP	PPA	PA 11
PP	PPA	PA 12
PA 6	PPA	PP
PA 11	PPA	PP
PA 12	PPA	PP
PA 6	PPA	PA 11
PA 6	PPA	PA 12
PA 11	PPA	PA 6
PA 12	PPA	PA 6
PA 11	PPA	PA 12
PA 12	PPA	PA 11
PE	BA	PPA
PP	BA	PPA
PA 6	BA	PPA
PA 11	BA	PPA
PA 12	BA	PPA
PE	PA 6/12	PPA
		PE

PP	PA 6/12	PPA	PP
PA 6	PA 6/12	PPA	PA 6
PA 11	PA 6/12	PPA	PA 11
PA 12	PA 6/12	PPA	PA 12
PE	PPA	BA	PE
PP	PPA	BA	PP
PA 6	PPA	BA	PA 6
PA 11	PPA	BA	PA 11
PA 12	PPA	BA	PA 12
PE	PPA	PA 6/12	PE
PP	PPA	PA 6/12	PP
PA 6	PPA	PA 6/12	PA 6
PA 11	PPA	PA 6/12	PA 11
PA 12	PPA	PA 6/12	PA 12
PPA	PE	BA	PPA
PPA	PE	BA	PE
PPA	PP	BA	PP
PPA	PA 6	BA	PA 6
PPA	PA 11	BA	PA 11
PPA	PA 12	BA	PA 12
PPA	PE	PA 6/12	PPA
PPA	PE	PA 6/12	PE
PPA	PP	PA 6/12	PP
PPA	PA 6	PA 6/12	PA 6
PPA	PA 11	PA 6/12	PA 11
PPA	PA 12	PA 6/12	PA 12
PPA	BA	PA 6/12	PPA
PPA	BA	PA 6/12	PE
PPA	BA	PA 6/12	PP
PPA	BA	PA 6/12	PA 6
PPA	BA	PA 6/12	PA 11
PPA	BA	PA 6/12	PA 12
PE	BA	PA 6/12	PPA
PP	BA	PA 6/12	PPA
PA 6	BA	PA 6/12	PPA
PA 11	BA	PA 6/12	PPA

PA 12	BA	PA 6/12	BA	PPA
PPA	PA 6	PA 6/12	BA	PPA
PPA	PA 6	PA 6/12	BA	PE
PPA	PA 6	PA 6/12	BA	PP
PPA	PA 6	PA 6/12	BA	PA 6
PPA	PA 6	PA 6/12	BA	PA 11
PPA	PA 6	PA 6/12	BA	PA 12
PPA	PA 11	PA 6/12	BA	PPA
PPA	PA 11	PA 6/12	BA	PE
PPA	PA 11	PA 6/12	BA	PP
PPA	PA 11	PA 6/12	BA	PA 6
PPA	PA 11	PA 6/12	BA	PA 11
PPA	PA 11	PA 6/12	BA	PA 12
PPA	PA 12	PA 6/12	BA	PPA
PPA	PA 12	PA 6/12	BA	PE
PPA	PA 12	PA 6/12	BA	PP
PPA	PA 12	PA 6/12	BA	PA 6
PPA	PA 12	PA 6/12	BA	PA 11
PPA	PA 12	PA 6/12	BA	PA 12
PA 6	PPA	PA 6/12	BA	PE
PA 6	PPA	PA 6/12	BA	PP
PA 6	PPA	PA 6/12	BA	PA 6
PA 6	PPA	PA 6/12	BA	PA 11
PA 6	PPA	PA 6/12	BA	PA 12
PA 11	PPA	PA 6/12	BA	PE
PA 11	PPA	PA 6/12	BA	PP
PA 11	PPA	PA 6/12	BA	PA 6
PA 11	PPA	PA 6/12	BA	PA 11
PA 11	PPA	PA 6/12	BA	PA 12
PA 12	PPA	PA 6/12	BA	PE
PA 12	PPA	PA 6/12	BA	PP
PA 12	PPA	PA 6/12	BA	PA 6
PA 12	PPA	PA 6/12	BA	PA 11
PA 12	PPA	PA 6/12	BA	PA 12
PA 6	PA 6/12	PPA	BA	PE
PA 6	PA 6/12	PPA	BA	PP

PA 6	PA 6/12	PPA	BA	PA 6
PA 6	PA 6/12	PPA	BA	PA 11
PA 6	PA 6/12	PPA	BA	PA 12
PA 11	PA 6/12	PPA	BA	PE
PA 11	PA 6/12	PPA	BA	PP
PA 11	PA 6/12	PPA	BA	PA 6
PA 11	PA 6/12	PPA	BA	PA 11
PA 11	PA 6/12	PPA	BA	PA 12
PA 12	PA 6/12	PPA	BA	PE
PA 12	PA 6/12	PPA	BA	PP
PA 12	PA 6/12	PPA	BA	PA 6
PA 12	PA 6/12	PPA	BA	PA 11
PA 12	PA 6/12	PPA	BA	PA 12
PA 6	PA 6/12	PE	BA	PPA
PA 6	PA 6/12	PP	BA	PPA
PA 6	PA 6/12	PA 6	BA	PPA
PA 6	PA 6/12	PA 11	BA	PPA
PA 6	PA 6/12	PA 12	BA	PPA
PA 11	PA 6/12	PE	BA	PPA
PA 11	PA 6/12	PP	BA	PPA
PA 11	PA 6/12	PA 6	BA	PPA
PA 11	PA 6/12	PA 11	BA	PPA
PA 11	PA 6/12	PA 12	BA	PPA
PA 12	PA 6/12	PE	BA	PPA
PA 12	PA 6/12	PP	BA	PPA
PA 12	PA 6/12	PA 6	BA	PPA
PA 12	PA 6/12	PA 11	BA	PPA
PA 12	PA 6/12	PA 12	BA	PPA

Or:

leitfähig/conductive (cond.)

Von Innen / Inner layer PPA cond	Nach Außen / PPA	Outer layer PE
PPA cond	PPA	PE

PPA cond	PPA		PP
PPA cond	PPA		PA 6
PPA cond	PPA		PA 11
PPA cond	PPA		PA 12
PPA cond	PE		PPA
PPA cond	PP		PPA
PPA cond	PA 6		PPA
PPA cond	PA 11		PPA
PA cond	PA 12		PPA
PPA cond	PPA	BA	PPA
PPA cond	PPA	BA	PE
PPA cond	PPA	BA	PP
PPA cond	PPA	BA	PA 6
PPA cond	PPA	BA	PA 11
PPA cond	PPA	BA	PA 12
PPA cond	PE	BA	PPA
PPA cond	PP	BA	PPA
PPA cond	PA 6	BA	PPA
PPA cond	PA 11	BA	PPA
PA cond	PA 12	BA	PPA
PPA cond	PPA	PA 6/12	PPA
PPA cond	PPA	PA 6/12	PE
PPA cond	PPA	PA 6/12	PP
PPA cond	PPA	PA 6/12	PA 6
PPA cond	PPA	PA 6/12	PA 11
PPA cond	PPA	PA 6/12	PA 12
PPA cond	PE	PA 6/12	PPA
PPA cond	PP	PA 6/12	PPA
PPA cond	PA 6	PA 6/12	PPA
PPA cond	PA 11	PA 6/12	PPA
PA cond	PA 12	PA 6/12	PPA
PPA cond	PE	PPA	PE
PPA cond	PP	PPA	PP
PPA cond	PA 6	PPA	PA 6
PPA cond	PA 11	PPA	PA 11

	PA cond	PA 12	PPA	PA 12
	PPA cond	PE	PPA	PP
	PPA cond	PE	PPA	PA 6
	PPA cond	PE	PPA	PA 11
	PPA cond	PE	PPA	PA 12
	PPA cond	PP	PPA	PE
	PA cond	PA 6	PPA	PE
	PA cond	PA 11	PPA	PE
	PA cond	PA 12	PPA	PE
	PPA cond	PP	PPA	PA 6
	PPA cond	PP	PPA	PA 11
	PPA cond	PP	PPA	PA 12
	PA cond	PA 6	PPA	PP
	PA cond	PA 11	PPA	PP
	PA cond	PA 12	PPA	PP
	PA cond	PA 6	PPA	PA 11
	PA cond	PA 6	PPA	PA 12
	PA cond	PA 11	PPA	PA 6
	PA cond	PA 12	PPA	PA 6
	PA cond	PA 11	PPA	PA 12
	PA cond	PA 12	PPA	PA 11
PPA cond	PE	BA	PPA	PE
PPA cond	PP	BA	PPA	PP
PPA cond	PA 6	BA	PPA	PA 6
PPA cond	PA 11	BA	PPA	PA 11
PA cond	PA 12	BA	PPA	PA 12
PPA cond	PE	PA 6/12	PPA	PE
PPA cond	PP	PA 6/12	PPA	PP
PPA cond	PA 6	PA 6/12	PPA	PA 6
PPA cond	PA 11	PA 6/12	PPA	PA 11
PA cond	PA 12	PA 6/12	PPA	PA 12
PPA cond	PE	PPA	BA	PE
PPA cond	PP	PPA	BA	PP
PPA cond	PA 6	PPA	BA	PA 6
PPA cond	PA 11	PPA	BA	PA 11

PA cond	PA 12	PPA	BA	PA 12
PPA cond	PE	PPA	PA 6/12	PE
PPA cond	PP	PPA	PA 6/12	PP
PPA cond	PA 6	PPA	PA 6/12	PA 6
PPA cond	PA 11	PPA	PA 6/12	PA 11
PA cond	PA 12	PPA	PA 6/12	PA 12
PPA cond	PPA	PE	BA	PPA
PPA cond	PPA	PE	BA	PE
PPA cond	PPA	PP	BA	PP
PPA cond	PPA	PA 6	BA	PA 6
PPA cond	PPA	PA 11	BA	PA 11
PPA cond	PPA	PA 12	BA	PA 12
PPA cond	PPA	PE	PA 6/12	PPA
PPA cond	PPA	PE	PA 6/12	PE
PPA cond	PPA	PP	PA 6/12	PP
PPA cond	PPA	PA 6	PA 6/12	PA 6
PPA cond	PPA	PA 11	PA 6/12	PA 11
PPA cond	PPA	PA 12	PA 6/12	PA 12
PPA cond	PPA	BA	PA 6/12	PPA
PPA cond	PPA	BA	PA 6/12	PE
PPA cond	PPA	BA	PA 6/12	PP
PPA cond	PPA	BA	PA 6/12	PA 6
PPA cond	PPA	BA	PA 6/12	PA 11
PPA cond	PPA	BA	PA 6/12	PA 12
PPA cond	PE	BA	PA 6/12	PPA
PPA cond	PP	BA	PA 6/12	PPA
PPA cond	PA 6	BA	PA 6/12	PPA
PPA cond	PA 11	BA	PA 6/12	PPA
PA cond	PA 12	BA	PA 6/12	PPA
PPA cond	PPA	PA 6	PA 6/12	PPA
PPA cond	PPA	PA 6	PA 6/12	PE
PPA cond	PPA	PA 6	PA 6/12	PP
PPA cond	PPA	PA 6	PA 6/12	PA 6
PPA cond	PPA	PA 6	PA 6/12	PA 11
PPA cond	PPA	PA 6	PA 6/12	PA 12

PPA cond	PPA	PA 11	PA 6/12	BA	PPA
PPA cond	PPA	PA 11	PA 6/12	BA	PE
PPA cond	PPA	PA 11	PA 6/12	BA	PP
PPA cond	PPA	PA 11	PA 6/12	BA	PA 6
PPA cond	PPA	PA 11	PA 6/12	BA	PA 11
PPA cond	PPA	PA 11	PA 6/12	BA	PA 12
PPA cond	PPA	PA 12	PA 6/12	BA	PPA
PPA cond	PPA	PA 12	PA 6/12	BA	PE
PPA cond	PPA	PA 12	PA 6/12	BA	PP
PPA cond	PPA	PA 12	PA 6/12	BA	PA 6
PPA cond	PPA	PA 12	PA 6/12	BA	PA 11
PPA cond	PPA	PA 12	PA 6/12	BA	PA 12
PPA cond	PA 6	PPA	PA 6/12	BA	PE
PPA cond	PA 6	PPA	PA 6/12	BA	PP
PPA cond	PA 6	PPA	PA 6/12	BA	PA 6
PPA cond	PA 6	PPA	PA 6/12	BA	PA 11
PPA cond	PA 6	PPA	PA 6/12	BA	PA 12
PPA cond	PA 11	PPA	PA 6/12	BA	PE
PPA cond	PA 11	PPA	PA 6/12	BA	PP
PPA cond	PA 11	PPA	PA 6/12	BA	PA 6
PPA cond	PA 11	PPA	PA 6/12	BA	PA 11
PPA cond	PA 11	PPA	PA 6/12	BA	PA 12
PA cond	PA 12	PPA	PA 6/12	BA	PE
PA cond	PA 12	PPA	PA 6/12	BA	PP
PA cond	PA 12	PPA	PA 6/12	BA	PA 6
PA cond	PA 12	PPA	PA 6/12	BA	PA 11
PA cond	PA 12	PPA	PA 6/12	BA	PA 12
PA cond	PA 6	PA 6/12	PPA	BA	PE
PA cond	PA 6	PA 6/12	PPA	BA	PP
PA cond	PA 6	PA 6/12	PPA	BA	PA 6
PA cond	PA 6	PA 6/12	PPA	BA	PA 11
PA cond	PA 6	PA 6/12	PPA	BA	PA 12
PA cond	PA 11	PA 6/12	PPA	BA	PE
PA cond	PA 11	PA 6/12	PPA	BA	PP
PA cond	PA 11	PA 6/12	PPA	BA	PA 6

PA cond	PA 11	PA 6/12	PPA	BA	PA 11
PA cond	PA 11	PA 6/12	PPA	BA	PA 12
PA cond	PA 12	PA 6/12	PPA	BA	PE
PA cond	PA 12	PA 6/12	PPA	BA	PP
PA cond	PA 12	PA 6/12	PPA	BA	PA 6
PA cond	PA 12	PA 6/12	PPA	BA	PA 11
PA cond	PA 12	PA 6/12	PPA	BA	PA 12
PA cond	PA 6	PA 6/12	PE	BA	PPA
PA cond	PA 6	PA 6/12	PP	BA	PPA
PA cond	PA 6	PA 6/12	PA 6	BA	PPA
PA cond	PA 6	PA 6/12	PA 11	BA	PPA
PA cond	PA 6	PA 6/12	PA 12	BA	PPA
PA cond	PA 11	PA 6/12	PE	BA	PPA
PA cond	PA 11	PA 6/12	PP	BA	PPA
PA cond	PA 11	PA 6/12	PA 6	BA	PPA
PA cond	PA 11	PA 6/12	PA 11	BA	PPA
PA cond	PA 11	PA 6/12	PA 12	BA	PPA
PA cond	PA 12	PA 6/12	PE	BA	PPA
PA cond	PA 12	PA 6/12	PP	BA	PPA
PA cond	PA 12	PA 6/12	PA 6	BA	PPA
PA cond	PA 12	PA 6/12	PA 11	BA	PPA
PA cond	PA 12	PA 6/12	PA 12	BA	PPA

Patent Claims

1. Multilayer tube suitable for use in vehicles, containing
5 at least one Polyphthalamide layer.
2. Multilayer tube as per claim 1 consisting of at least three layers, wherein the Polyphthalamide layer is a barrier layer.
3. Multilayer tube as per claim 1 or 2, wherein the outer
10 and / or inner layer consist(s) of Polyphthalamide.
4. Multilayer tube as per claim 1 to 3, comprising at least one layer of Polyamide, preferably selected from the group 6,6-Polyamide, 11,11-Polyamide, 12,12-Polyamide, Copolymer from 6,6-Polyamide and 12,12-Polyamide.
- 15 5. Multilayer tube as per claim 1 to 4, wherein at least one Polyamide layer is a bonding agent.
6. Multilayer tube as per claim 1 to 5, containing at least one layer of Polyethlyene or Polypropylene or a Copolymer therof.
- 20 7. Multilayer tube as per one of the claims 1 to 6, containing at least one layer of an adhesive or bonding agent.
8. Multilayer tube as per one of the claims 1 to 7, wherein
25 at least one Polyphthalamide-layer or Polyamide-layer is conductive.
9. Multilayer tube as per one of the claims 1 to 8, containing additions of softeners, flame restraints, anti-oxidation means or stabilizing agents.
10. Multilayer tube as per one of the claims 1 to 9,
30 selected from the group

PPA - PA 6 - PA 6/12 (bonding agent) - PA 12,

PPA - PA 6 - PA 6/12 (bonding agent) - PPA,

PPA - PA 6/12 (bonding agent) - PA 12,

PA 6 - PPA - PA 6,

5 PA 12 - PPA - PA 12,

PPA - PA 6 (bonding agent) - PPA,

PPA cond. - PPA - PA 6 (bonding agent) - PPA.

11. Multilayer tube as per one of the claims 1 to 10,
characterized in that the hydrocarbon-permission level
10 is equal or below 0,5 g/m² for a time frame of 24 h (1
d).

12. Multilayer tube as per one of the claims 1 to 11,
wherein the tube comprises an outer cover.

13. Use of a multilayer tube as per one of the claims 1 to
15 12, as fuel and vapor tube.

INTERNATIONAL SEARCH REPORT

International Application No
PCT/EP2004/010059

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 B32B27/34 F16L11/04 F16L9/12

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 B32B F16L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ, COMPENDEX

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 1 195 244 A (TOKAI RUBBER IND LTD) 10 April 2002 (2002-04-10) claim 1 paragraph '0001! paragraph '0016! figures 1,2 -----	1-3,13
X	US 2003/124281 A1 (MONSHEIMER SYLVIA ET AL) 3 July 2003 (2003-07-03) claims 1,6,8,10,13,14 paragraph '0038! -----	1,8,13
X	FR 2 766 548 A (HUTCHINSON) 29 January 1999 (1999-01-29) claim 1 ----- -/-	1-3,13

Further documents are listed in the continuation of box C.

Patent family members are listed in annex.

° Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

15 November 2004

Date of mailing of the international search report

22/11/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Hillebrand, G

INTERNATIONAL SEARCH REPORT

International Application No
PCT/EP2004/010059

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 175 238 A (MATLACK JOHN D ET AL) 29 December 1992 (1992-12-29) claim 1 column 2, line 11 -----	1
P,X	US 2003/192612 A1 (MILHAS PIERRE) 16 October 2003 (2003-10-16) claim 1 -----	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP2004/010059

Patent document cited in search report	Publication date	Patent family member(s)			Publication date
EP 1195244	A 10-04-2002	JP	2002181253 A		26-06-2002
		JP	2002181254 A		26-06-2002
		JP	2002181249 A		26-06-2002
		EP	1195244 A1		10-04-2002
		US	2002074050 A1		20-06-2002
US 2003124281	A1 03-07-2003	DE	10164408 A1		17-07-2003
		BR	0205484 A		27-07-2004
		CA	2415138 A1		28-06-2003
		CN	1428236 A		09-07-2003
		EP	1323973 A2		02-07-2003
		JP	2003269682 A		25-09-2003
FR 2766548	A 29-01-1999	FR	2766548 A1		29-01-1999
US 5175238	A 29-12-1992	CA	2020481 A1		22-01-1991
		EP	0409666 A2		23-01-1991
		JP	3115460 A		16-05-1991
US 2003192612	A1 16-10-2003	FR	2838501 A1		17-10-2003
		BR	0300879 A		17-08-2004
		CA	2424533 A1		15-10-2003
		EP	1355098 A1		22-10-2003